Pneumatic Drip Leg



- Simple, effective water removal Reduced air velocity from line allows water droplets to fall out of the air stream and collect for discharge
- Durable welded carbon steel construction

SMC.

- Easy to incorporate as part of a machine drop from an overhead distribution line
- NPT or G thread models available

Specifications

| Max. Working Pressure | 150 psig (1.0 MPa) | | | |
|-----------------------|--------------------|--|--|--|
| Proof Pressure | 220 psig (1.5 MPa) | | | |
| Material | Carbon Steel | | | |

Part Numbers

| In/Out Connection | Model Number | | | | | |
|----------------------|-------------------|------------------|--|--|--|--|
| Size | NPTF | ISO G | | | | |
| 1/2" | FAPP-T04-DUP01533 | FAPP-04-DDL00026 | | | | |
| 3/4" | FAPP-T06-DUP01534 | FAPP-06-DDL00006 | | | | |
| 1" | FAPP-T10-DUP01535 | FAPP-08-DDL00007 | | | | |
| 1-1/2" | FAPP-T14-DUP01536 | FAPP-12-DDL00008 | | | | |
| 2" | FAPP-T20-DUP01537 | FAPP-16-DDL00012 | | | | |

Pneumatic Drip Leg

| Model Number | | y OD A | | utlet Face to C/L OAL B C | | | Outlet Offset from Top D | | IN/Out Port | Drain Port |
|-------------------|------|-----------|------|------------------------------|-------|-----|-----------------------------|-----|----------------|---------------|
| | in | mm | in | mm | in | mm | in | mm | | 1 010 |
| FAPP-T04-DUP01533 | 1.73 | 44 | 1.93 | 49 | | | 5.04 | 128 | NPT 1/2" | NPT 3/8" |
| FAPP-T06-DUP01534 | 2.36 | 60 | 2.36 | 60 | 14.96 | 380 | | | NPT 3/4" | |
| FAPP-T10-DUP01535 | 2.99 | 76 | 2.83 | 72 | | | | | NPT 1" | |
| FAPP-T14-DUP01536 | 4.49 | 114 | 3.82 | 97 | 17.91 | 455 | | | NPT 1-1/2" | |
| FAPP-T20-DUP01537 | 5.98 | 152 | 4.57 | 116 | 18.31 | 465 | | 153 | NPT 2" | |
| FAPP-04-DDL00026 | 1.73 | 44 | 1.89 | 48 | | | | 128 | G 1/2" | G 3/8" |
| FAPP-06-DDL00006 | 2.36 | 60 | 2.36 | 60 | 14.96 | 380 | 5.04 | | G 3/4" | |
| FAPP-08-DDL00007 | 2.99 | 76 | 2.83 | 72 | | | 5.04 | | G 1" | |
| FAPP-12-DDL00008 | 4.49 | 114 | 3.82 | 97 | 17.91 | 455 | | | G 1-1/2" | |
| FAPP-16-DDL00012 | 6.06 | 154 | 4.53 | 115 | 18.31 | 465 | 6.02 | 153 | G 2" | |

Related Products

| Description | Connection | Part Number |
|---------------------------------------|------------|-----------------|
| Float Type Auto | NPT 3/8" | AD402-N03C-2Z-A |
| Drain Vavle - N.C. | G 3/8" | AD402-F03C-2-A |
| Float Type Auto Drain Vavle - N.O. | NPT 3/8" | AD402-N03D-2Z-A |
| | G 3/8" | AD402-F03D-2-A |
| Timer Drain Valve | NPT 3/8" | ADM200-N03 |
| | G 3/8" | ADM200-F03 |
| Heavy Duty | NPT 1/2" | ADH400C-N04 |
| Auto Drain | G 1/2" | ADH400C-F04 |



For International inquires: www.smcworld.com SMC Automation (Canada) Ltd. www.smcpneumatics.ca

Purchase with AD402-N03 Auto Drain

YV-RRD-2.5M

SMC Corporation of America 10100 SMC Blvd. Noblesville, IN 46060

(800) SMC.SMC1 (762 - 7621)

All reasonable efforts to ensure the accuracy of the information detailed in this flyer were made at the time of publishing. However, SMC can in no way warrant the information herein contained as specifications are subject to change without notice.