

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2322935-2  
**Report Reference** MH11419-20230630  
**Date** 17-Nov-2023

**Issued to:** SMC CORP  
4-14-1 SOTO-KANDA  
CHIYODA-KU, Tokyo 101-0021  
Japan

**This is to certify that  
representative samples of**

YIOZ8 - Valves, Electrically Operated Certified for Canada -  
Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

**Standard(s) for Safety:** CSA C22.2 No. 139, 3rd Ed., Issue Date: 2010-06-01

**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

*Deborah Jennings-Conner*

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2322935-2  
**Report Reference** MH11419-20230630  
**Date** 17-Nov-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

| <b>Model</b>  | <b>Category Description</b> |
|---|-----------------------------|
| <b>D or Y</b> , 25A-VP3 or VP3, followed by 46, followed by E, followed by 5, followed by D or Y, with or without Z, with or without E, followed by 1, with or without R, with or without S, with or without X660.        | General-purpose valve       |
| <b>KO or KVO</b> , 25A-VP3 or VP3, followed by 46, followed by E, followed 5, followed by KO or KVO, followed by Z, with or without E, followed by 1, with or without R, with or without S, with or without X660 .        | General-purpose valve       |
| <b>DO or YO</b> , 25A-VP3 or VP3, followed by 46, followed by E, followed by 5, followed by DO or YO, with or without E, followed by 1, with or without R, with or without S, with or without X660.                       | General-purpose valve       |
| <b>KVO</b> , 25A-VP3 or VP3, followed by 46, followed by E, followed by 5, followed by KVO, followed by Z, with or without E, followed by 1, with or without R, with or without S, followed by X661.                      | General-purpose valve       |
| <b>KO or KVO</b> , 25A-VP5 or VP5, followed by 46, followed by E, followed by 5, followed by KO or KVO, followed by Z, with or without E, followed by 1, with or without R, with or without S, followed by X661.          | General-purpose valve       |
| <b>DO or DYO</b> , 25A-VP5 or VP5, followed by 46, followed by E, followed by 5, followed by DO or YO, with or without A or E, followed by 1, with or without R, with or without S, with or without X660.                 | General-purpose valve       |
| <b>KO or KVO</b> , 25A-VP5 or VP5, followed by 46, followed by E, followed by 5, followed by KO or KVO, followed by Z, with or without A or E, followed by 1, with or without R, with or without S, with or without X660. | General-purpose valve       |
| <b>D or Y</b> , 25A-VP5 or VP5, followed by 46, followed by E, followed by 5, followed by D or Y, with or without Z, with or without A or E, followed by 1, with or without R, with or without S, with or without X660.   | General-purpose valve       |
| <b>KO or KVO</b> , 25A-VP7 or VP7, followed by 46, followed by E, followed by 5, followed by KO or KVO, followed by Z, with or without E, followed by 1, with or without R, with or without S, followed by X661.          | General-purpose valve       |
| <b>DO or YO</b> , 25A-VP7 or VP7, followed by 46, followed by E, followed by 5, followed by DO or YO, with or without A or E, followed by 1, with or without R, with or without S, with or without X660.                  | General-purpose valve       |

*Deborah Jennings-Conner*  
Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-2322935-2  
**Report Reference** MH11419-20230630  
**Date** 17-Nov-2023

|   |                       |
|---|-----------------------|
| <b>KO or KVO</b> , 25A-VP7 or VP7, followed by 46, followed by E, followed by 5, followed by KO or KVO, followed by Z, with or without A or E, followed by 1, with or without R, with or without S, with or without X660.   | General-purpose valve |
| <b>D or Y</b> , 25A-VP7 or VP7, followed by 46, followed by E, followed by 5, followed by D or Y, with or without Z, with or without A or E, followed by 1, with or without R, with or without S, with or without X660.   | General-purpose valve |
| <b>D or Y</b> , 25A-VP9 or VP9, followed by 46, followed by E, followed by 5, followed by D or Y, with or without Z, with or without E, followed by 1, with or without R, with or without S, with or without X660.  | General-purpose valve |
| <b>DO or YO</b> , 25A-VP9 or VP9, followed by 46, followed by E, followed by 5, followed by DO or YO, with or without E, followed by 1, with or without R, with or without S, with or without X660.   | General-purpose valve |
| <b>KO</b> , 25A-VP9 or VP9, followed by 46, followed by E, followed by 5, followed by KO, followed by Z, with or without E, followed by 1, with or without R, with or without S, followed by X661.  | General-purpose valve |
| <b>KO or KVO</b> , 25A-VP9 or VP9, followed by 46, followed by E, followed by 5, followed by KO or KVO, followed by Z, with or without E, followed by 1, with or without R, with or without S, with or without X660.  | General-purpose valve |
| <b>D, Y, KO or KVO</b> , VP5, followed by 46, with or without R, followed by 5, followed by D, Y, KO or KVO, followed by Z, followed by 1, with or without M or S1, with or without R, followed by S or D, with or without S, with or without F or N, with or without X660. | General-purpose valve |

*Deborah Jennings-Conner*

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

