

CERTIFICATE OF COMPLIANCE

Certificate Number 20161222-E327452
Report Reference E327452-20100809
Issue Date 2016-DECEMBER-22

Issued to: SMC CORP
TSUKUBA TECHNICAL CENTER, 4-2-2 KINUNODAI,
TSUKUBAMIRAI-SHI, IBARAKI-KEN 300-2493 JAPAN

**This is to certify that
representative samples of** VALVES, ELECTRIC FOR USE IN HAZARDOUS
LOCATIONS

Please see addendum

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 429 & CSA C22.2 No. 139-1982 - Electrically Operated
Valves. UL 913 - Intrinsically Safe Apparatus and
Associated Apparatus for Use in Class I, II, and III, Division
1, Hazardous (Classified) Locations. CAN/CSA C22.2 No.
157-92 - Intrinsically Safe and Non-incendive Equipment for
Use in Hazardous Locations.

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20161222-E327452
Report Reference E327452-20100809
Issue Date 2016-DECEMBER-22

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class I, Groups A, B, C, D Hazardous Locations.

Intrinsically Safe 5 Port Solenoid Valve, Series 53-SY followed by 5, 7, or 9; followed by 1, 2, 3, 4, or 5; followed by 20, followed by L or LL; followed by 3, 6, 10, 15, 20, 30, or 100; may be followed by D or E; followed by 01, 02, 03, C4, C6, C8, C10, C12, N3, N7, N9, or N11; may be followed by F, N, or T; may be followed by F1 or F2; intrinsically safe when installed per drawing No. 53-SY-OMO0001.

Intrinsically Safe 3 Port Solenoid Valve, Series 53-SY followed by 5; followed by A, B, or C; followed by 20; followed by L or LL; followed by 3, 6, 10, 15, 20, 30 or 100; may be followed by D or E; followed by 01, -C4, C6, C8, N3, N7 or N9; may be followed by F, N, or T; may be followed by F1 or F2; intrinsically safe when installed per drawing No. 53-SY-OMO0001.

Class I, Groups A, B, C, D; Class II, Groups E, F, G; Class III Hazardous Locations.

Intrinsically Safe 5 Port Solenoid Valve, Series 53-SY followed by 5, 7, or 9; followed by 1, 2, 3, 4, or 5; followed by 20; followed by TT; followed by 3, 6, 10, 15, 20, 30, or 100; may be followed by D or E; followed by 01, 02, 03, C4, C6, C8, C10, C12, N3, N7, N9, or N11; may be followed by F, N, or T; may be followed by F1 or F2; intrinsically safe when installed per drawing No. 53-SY-OMO0001.

Intrinsically Safe 3 Port Solenoid Valve, Series 53-SY followed by 5; followed by A, B, or C; followed by 20; followed by TT; followed by 3, 6, 10, 15, 20, 30 or 100; may be followed by D or E; followed by 01, C4, C6, C8, N3, N7 or N9; may be followed by F, N, or T; may be followed by F1 or F2; intrinsically safe when installed per drawing No. 53-SY-OMO0001.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

