

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L000434-8
Report Reference MH11419-20150213
Date 11-Sep-2023

Issued to: SMC CORP
Tsukuba Technical Center
4-2-2 Kinunodai
Tsukubamirai-Shi, Ibaraki 300-2493
Japan

This is to certify that representative samples of YIOZ8 - Valves, Electrically Operated Certified for Canada - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CSA C22.2 No. 139, 3rd Ed., Issue Date: 2010-06-01

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L000434-8
Report Reference MH11419-20150213
Date 11-Sep-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Manifold , 10-SS or SS, followed by 5Y3, followed by 51, followed by S0, followed by 02, 04, 08 or 16, followed by U, followed by X207.	General-purpose valve
Base Mounted , 25A-SY, followed by 5 or 7, followed by 1, 2, 3, 4, 5, A, B or C, followed by 0, followed by 0, with or without R, with or without H, with or without B, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, with or without D, E or F, followed by 1, may be followed by -NA.	General-purpose valve
Top Ported , 25A-SY, followed by 5 or 7, followed by 1, 2, 3, 4, 5, A, B or C, followed by 3, followed by 0, with or without R, with or without H, with or without B, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, with or without D, E or F, followed by 1, followed by C4, C6, C8, C10, C12 or 02, may be followed by -NA.	General-purpose valve
Top Ported , HF1-SY, 10-SY or SY, followed by 3, 5 or 7, followed by 1, 2, 3, 4, 5, A, B or C, followed by 3, followed by 0 or 1, with or without R, with or without H, with or without B or K, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, with or without D, E or F, followed by 1, followed by C2, C3, C4, C6, C8, C10, C12, M5, N1, N3, N7, N9, N11, 01 or 02, with or without B, K or H, with or without X90, X100, X200 or X320, may be followed by -NA.	General-purpose valve
Base Mounted , HF1-SY, 10-SY or SY, followed by 3 or 5, followed by 1, 2, 3, 4, 5, A, B or C, followed by 0, followed by 0 or 1, with or without R, with or without H, with or without B or K, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, followed by 1, followed by HC, with or without X90, X100, X200 or X320, may be followed by -NA.	General-purpose valve
Base Mounted , HF1-SY, 10-SY or SY,, followed by 3, 5 or 7, followed by 1, 2, 3, 4, 5, A, B or C, followed by 0, followed by 0 or 1, with or without R, with or without H, with or without B or K, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, with or without D, E or F, followed by 1, with or without B, K or H, with or without X90, X100, X200 or X320, may be followed by -NA.	General-purpose valve


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L000434-8
Report Reference MH11419-20150213
Date 11-Sep-2023

SS, followed by 5Y3-51S0- followed by 02, 04, 08 or 16, followed by U-X207	General purpose valves
SS5Y3-51S0-02U-X207	Manifolds
SS5Y3-51S0-04U-X207	Manifolds
SS5Y3-51S0-08U-X207	Manifolds
SS5Y3-51S0-16U-X207	Manifolds
SY, followed by 3 or 5, followed by 1, 2, 3, 4, 5, A, B or C, followed by 0, followed by 0 or 1, with or without R, with or without H, with or without B or K, with or without T, followed by 5 or 6, with or without R, U, S, Z, NS or NZ, followed by 1, followed by HC, with or without X90, X100, X200 or X320.	General purpose valves
SY3, SY5 or SY7, , followed by 1, 2, 3, 4, 5, A, B or C, followed by 1, followed by 0 or 1, may be followed by R, may be followed by H, may be followed by B or K, may be followed by T, followed by 5 or 6, may be followed by R, U, S, Z, NS or NZ, may be followed by D, E or F, followed by 1, followed by C2, C3, C4, C6, C8, C10, C12, M5, N1, N3, N7, N9, N11, 01 or 02, may be followed by B, K or H.	Blanking plates
(Base Mounted) , SY5, followed by 1, followed by 0, followed by 0, with or without T, followed by 5 or 6, followed by NZ, followed by 1, with or without K or H, followed by X310.	General-purpose valve
(Top Ported) , SY5, followed by 1, followed by 3, followed by 0, with or without T, followed by 5 or 6, followed by NZ, followed by 1, followed by 01, C4, C6 or C8, with or without F, N or T, with or without K or H, followed by X310.	General-purpose valve


 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>