

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L001101-2
Report Reference MH11419-20081002
Date 11-Sep-2023

Issued to: SMC CORP
Tsukuba Technical Center
4-2-2 Kinunodai
Tsukubamirai-Shi, Ibaraki 300-2493
Japan

This is to certify that representative samples of YIOZ2 - Valves, Electrically Operated - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 429 - 7th Ed - Issued 6 Nov 2013 - Revised 16 Jan 2020

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L001101-2
Report Reference MH11419-20081002
Date 11-Sep-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
10-SJ, followed by 3, followed by A6, with or without T, with or without N, followed by 5 or 6, with or without N, followed by C, F, M, MN or MO, followed by U or Z, with or without J, with or without D, with or without D, with or without P.	General-purpose valve
10-SS3J, followed by 3, followed by V, followed by 60, followed by 01 through 20, followed by B, D, M, or U, with or without B or L, with or without 2 through 20.	General-purpose valve
10-SS5J, followed by 2 or 3, with or without M, followed by 60, with or without L, followed by F, P, PG, J or PH, followed by D followed by 1 or 2, followed by 01 through 24, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 24.	General-purpose valve
KJ, followed by H, L, or W, followed by 01 through 07, followed by C1 or C2.	General-purpose valve
SJ, followed by 3, followed by A6, with or without T, with or without N, followed by 5 or 6, with or without N, followed by C, F, M, MN or MO, followed by U or Z, with or without J, with or without D, with or without D, with or without P.	General-purpose valve
SJ or 10-SJ, followed by 2 or 3, followed by 1, 2, 3, 4, 5, A, B or C, followed by 60, with or without R, with or without E, K or P, with or without T, with or without N, followed by 5 or 6, with or without N, followed by C, F, M, MN or MO, followed by U or Z, with or without J, with or without D or F, followed by B2, B4, B6, BN1, BN3, BN7, C0, C2, C4, C6, L2, L4, L6, LN1, LN3, LN7, M3, M5, N1, N3 or N7, with or without D.	General-purpose valve
SS3J, followed by 3, followed by V, followed by 60, followed by 01 through 20, followed by B, D, M, or U, with or without B or L, with or without 2 through 20.	General-purpose valve
SS3J or, 10-SS3J, followed by 3, followed by V, followed by 60S6B, with or without N, followed by D, followed by 01 through 08, followed by B, D, M, or U, with or without B or L, with or without 2 through 08.	General-purpose valve
SS3J or 10-SS3J, followed by 3, followed by V, followed by 60, followed by G, followed by D, followed by 01 through 08, followed by B, D, M, or U, with or without B or L, with or without 2 through 8.	General-purpose valve


Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L001101-2
Report Reference MH11419-20081002
Date 11-Sep-2023

SS3J or 10-SS3J,, followed by 3, followed by V, followed by 60, with or without L, followed by F, P, PG, J, or PH, followed by D, followed by 1 or 2, followed by 01 through 12, followed by B, D, M, or U, with or without B or L, with or without 2 through 12.	General-purpose valve
SS3J or 10-SS3J, followed by 3, , followed by V, followed by 60S, followed by 0, Q, Q1, Q2, Q3, V, or V2, with or without A, with or without N, with or without D, followed by 01 through 16, followed by B, D, M, or U, with or without B or L, with or without 2 through 16.	General-purpose valve
SS5J, followed by 2 or 3, with or without M, followed by 60, with or without L, followed by F, P, PG, J or PH, followed by D followed by 1 or 2, followed by 01 through 24, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 24.	General-purpose valve
SS5J or, 10-SS5J, followed by 2 or 3, with or without M, followed by 60S6B, with or without N, followed by D, followed by 01 through 16, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 16.	General-purpose valve
SS5J or 10-SS5J, followed by 2 or 3, with or without M, followed by 60, followed by G, followed by D, followed by 01 through 16, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 16.	General-purpose valve
SS5J or 10-SS5J, , followed by 2 or 3, with or without M, followed by 60, followed by 01 through 20, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 20.	General-purpose valve
SS5J or 10-SS5J,, followed by 2 or 3, with or without M, followed by 60S, followed by 0, Q, Q1, Q2, Q3, V or V2, with or without A, with or without N, with or without D, followed by 01 through 32, followed by B, D, M, or U, with or without R, RS, or S, with or without B or L, with or without 2 through 32.	General-purpose valve

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>