

3-Screen Display

High-Precision Digital Pressure Switch

Air	1.0 MPa/1.6 MPa	ISE70	ISE71
General Fluids	1.0 MPa/2.0 MPa	ISE70G	ISE75G
	5.0 MPa/10 MPa	ISE76G	ISE77G

IO-Link

CE C US

RoHS

IP67

It is possible to change the settings while checking the measured value.

Main screen

Measured value (Current pressure value)

Sub screen

Label (Display item), Set value (Threshold value)

Visualization of Settings


Set value (Threshold value)	P.L
Hysteresis value	H.L
Peak value	H.H
Bottom value	H.Lo



Angled display Good visibility from various mounting positions



Rotating display



Install a switch with a wrench.



336°

After installation, the display can be rotated to an easy-to-see direction by securing the body by hand.


ISE7□/7□G Series



CAT.ES100-123B

Visualization of Settings

The sub screen (label) shows the item to be set.




Mode Examples

Hysteresis mode




Window comparator mode




Simple 3-Step Setting

When the SET button is pressed and the set value (P_1) is being displayed, the set value (threshold value) can be set. When the SET button is pressed and the hysteresis value (H_1) is being displayed, the hysteresis value can be set.




With a snap shot function for set value reading

Pressing the UP and DOWN buttons simultaneously for a minimum of 1 second will make the set value (threshold value) the same as the current pressure value.



NPN/PNP Switch Function


Both NPN and PNP are available.
The number of stock items can be reduced.



Other Sub Screen Display

The peak value, bottom value, or both values can be displayed on one screen!

* Peak and bottom values are maintained even if the power supply is cut.



Output mode/Output type display				Rated range display	Level bar display	Pressure unit display			
Hysteresis mode	Window comparator mode	Positive pressure range				kPa	MPa	psi*1	bar*1
Normal output	Reversed output	Normal output	Reversed output	P0.51	0.000 0.000	KPA	MPA	PSI	BAR

*1 "psi" and "bar" can be selected when the unit selection function is available.

* A combination of the displays shown above and the set values can be displayed on the 2 sub screens.

Convenient Functions

Security code


The key-lock function keeps unauthorized persons from tampering with the settings.

Power-saving mode

Power consumption is reduced by turning off the monitor. (Reduce power consumption by approx. 60%.)

Resolution switch function

Reduces monitor flickering



Applied pressure error

When the applied pressure exceeds the rated pressure, the pressure application is counted as an applied pressure error (the maximum number of applied pressure errors is 1000 counts).




The number of applied pressure errors



3 Setting Modes


Select the setting mode that best meets your needs.



* The chart above shows OUT1 operations. The Function Selection Mode for OUT2 is set using "F2." "2" will be displayed instead of "1" in the illustration above. (Example) P₁ → P₂

IO-Link Compatible

Visualization of operation/equipment status/Remote monitoring and control by communication



Implement diagnostic bits in the process data.

The diagnostic bit in the cyclic process data makes it easy to find problems with the equipment. It is possible to find problems with the equipment in real time using the cyclic (cycle) data and to monitor such problems in detail with the noncyclic (aperiodic) data.

Process Data

Bit offset	Item	Note
0	OUT1 output	0: OFF 1: ON
1	OUT2 output	0: OFF 1: ON
2	Diagnosis	0: Normal 1: Abnormal
3 to 15	Measured pressure value	Unsigned 13 bit

Diagnosis items

- Internal product malfunction
- Outside of zero-clear range
- Outside of rated pressure range
- Upper temperature limit exceeded inside the product

Bit offset	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0
Item	Measured pressure value													Diagnosis	OUT2	OUT1

Display function

Displays the output communication status and indicates the presence of communication data













Operation and Display

Communication with master	IO-Link status indicator	Status	Screen display*3	Description
Yes	COM*1	Normal	Operate	Normal communication status (readout of measured value)
			Start up	At the start of communication
			Preoperate	
	(Flashing)*2	Abnormal	Version does not match	IO-Link version does not match that of the master. The master uses version 1.0.
			Lock	Back-up and re-store required due to data storage lock
No	OFF	Communication disconnection	MODE aPE	Normal communication was not received for 1 second or longer.
			MODE Strt	
No	OFF	SIO mode	MODE PrE	General switch output
			MODE S io	

*1 The COM indicator is ON when communication with the master is established. *2 In IO-Link mode, the IO-Link indicator is ON or flashes. *3 When the sub screen is set to Mode

Introduction of Series

		ISE70/71 p. 6		ISE70G/75G/76G/77G p. 8			
							
Applicable fluid		 Air		 General fluids			
Series		ISE70	ISE71	ISE70G	ISE75G	ISE76G	ISE77G
Rated pressure range							
Withstand pressure		1.5 MPa	2.4 MPa	3.0 MPa	5.0 MPa	12.5 MPa	30 MPa
Power supply voltage	When used as a switch output device	12 to 24 VDC ±10% with 10% voltage ripple or less					
	When used as an IO-Link device	18 to 30 VDC, including ripple (p-p) 10%					
Temperature characteristics		±2% F.S. (25°C standard)		±3% F.S. (ISE70G)/±5% F.S. (ISE75G/76G/77G)			
Repeatability		±0.5% F.S.					
Hysteresis		Hysteresis mode: Variable Window comparator mode: Variable					
Output type		Select from NPN or PNP open collector.					
Number of screens/ Display type		3-screen/2-color display					
Enclosure		IP67					
Materials of parts in contact with fluid		Sensor pressure receiving area: Silicon Piping port: C3604 (Electroless nickel plating) O-ring: HNBR		Sensor pressure receiving area: Al2O3 (Alumina 96%) Piping port: C3604 (Electroless nickel plating) O-ring: FKM + Grease (ISE70G) Square ring: FKM (ISE75G/76G/77G)			
Piping		Rc1/4, NPT1/4, G1/4 (ISO 1179-1 compliant)					
Option		Lead wire with M12 connector, Bracket					
Note		Selectable pressure unit, Anti-chattering function, Display calibration function, Power-saving mode, Sub screen setting function					

For General Fluids: Remote Type Variations

PSE56□ Series

- Material of parts in contact with fluid: Stainless steel 316L
- Suitable for a wide variety of fluids
- Analog output (Voltage/Current)
- Select from a face seal or compression fitting.




PSE57□ Series

- Withstand voltage: 500 VAC
- Materials of parts in contact with fluid
Piping port: C3604 + Nickel plating
Pressure sensor: Al₂O₃ (Alumina 96%)
O-ring: FKM + Grease (PSE570/573/574)
Square ring: FKM (PSE575/576/577)




Select either the integrated type or the remote type according to the application.

<Integrated type>



<Remote type>



CONTENTS

3-Screen Display High-Precision Digital Pressure Switch: For Air ISE70/71 Series

How to Order	p. 6
Options/Part Nos.	p. 6
Specifications	p. 7
Set Pressure Range and Rated Pressure Range	p. 10
Internal Circuits and Wiring Examples	p. 10
Dimensions	p. 11
Function Details	p. 12
Safety Instructions	Back cover



3-Screen Display High-Precision Digital Pressure Switch: For General Fluids ISE70G/75G/76G/77G Series

How to Order	p. 8
Options/Part Nos.	p. 8
Specifications	p. 9
Set Pressure Range and Rated Pressure Range	p. 10
Internal Circuits and Wiring Examples	p. 10
Dimensions	p. 11
Function Details	p. 12
Safety Instructions	Back cover



3-Screen Display



IO-Link



c



RoHS

High-Precision Digital Pressure Switch: For Air

ISE70/71 Series



How to Order

ISE70 - 02 - L2 - M

Pressure range

Symbol	Description
ISE70	0 to 1 MPa
ISE71	0 to 1.6 MPa

Piping specification

Symbol	Description
02	Rc1/4
N02	NPT1/4
F02	G1/4*1

*1 ISO 1179-1 compliant

Output specification*1

Symbol	Description
L2	IO-Link: Switch output 1 + Switch output 2 (Switch output: NPN or PNP switching type)

*1 Refer to pages 7 and 10 for details.

Unit specification

Symbol	Description
Nil	Unit selection function*1
M	SI unit only*2

*1 Under the New Measurement Act, switches with the unit selection function are not permitted for use in Japan.

*2 Fixed unit: MPa, kPa

Option 3

Symbol	Description
Nil	Operation manual
Y	None
K	Operation manual + Calibration certificate
T	Calibration certificate

Option 2





Symbol	Description
Nil	None
A	Bracket A (Interchangeable with ISE70)
B	Bracket B

Option 1

Symbol	Description
Nil	None
S	Lead wire with M12 connector (Straight, 5 m)
L	Lead wire with M12 connector (Right-angled, 5 m)

Options/Part Nos.

When only optional parts are required, order with the part numbers listed below.

Description	Part no.	Note
Bracket A 	ZS-50-A	Interchangeable with ISE70 With 2 mounting screws (M4 x 6L)
Bracket B 	ZS-50-B	With 2 mounting screws (M4 x 6L)
Lead wire with M12 connector: Straight 	ZS-31-B	Lead wire length: 5 m
Lead wire with M12 connector: Right-angled 	ZS-31-C	Lead wire length: 5 m

ISE70/71 Series

Specifications

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Model			ISE70	ISE71
Applicable fluid			Air, Non-corrosive gas, Non-flammable gas	
Pressure	Rated pressure range		0 to 1.000 MPa	0 to 1.600 MPa
	Display/Set pressure range		−0.105 to 1.050 MPa	−0.105 to 1.680 MPa
	Display/Smallest settable increment		0.001 MPa	0.001 MPa
	Withstand pressure		1.5 MPa	2.4 MPa
Power supply	Power supply voltage	When used as a switch output device	12 to 24 VDC ±10% with 10% voltage ripple or less	
		When used as an IO-Link device	18 to 30 VDC, including ripple (p-p) 10%	
	Current consumption		35 mA or less	
	Protection		Polarity protection	
Accuracy	Display accuracy		±2% F.S. ±1 digit (Ambient temperature of 25 ±3°C)	
	Repeatability		±0.5% F.S.	
	Temperature characteristics		±2% F.S. (25°C standard)	
Switch output (SIO mode)	Output type		Select from NPN or PNP open collector output.	
	Output mode		Hysteresis, Window comparator, Error output, Output OFF	
	Switch operation		Normal output, Reversed output	
	Maximum load current		80 mA	
	Maximum applied voltage		30 V (NPN output)	
	Internal voltage drop (Residual voltage)		1.5 V or less (at load current of 80 mA)	
	Delay time*1		1.5 ms or less, variable from 0 to 60 s/0.01 s increments	
	Hysteresis	Hysteresis mode	Variable from 0*2	
		Window comparator mode		
	Short circuit protection		Yes	
Display	Unit*3		MPa, kPa, kgf/cm², bar, psi	
	Display type		LCD	
	Number of screens		3-screen display (Main screen, Sub screen x 2)	
	Display color		Main screen: Red/Green, Sub screen: Orange	
	Number of display digits		Main screen: 4 digits (7 segments), Sub screen: 4 digits (Upper 1 digit 11 segments, 7 segments for other)	
	Indicator light		Lights up when switch output is turned ON (OUT1, OUT2: Orange)	
Digital filter*4			Variable from 0 to 30 s/0.01 s increments	
Environment	Enclosure		IP67	
	Withstand voltage		1000 VAC for 1 minute between terminals and housing	
	Insulation resistance		50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing	
	Operating temperature range		Operating: 0 to 50°C, Stored: −10 to 60°C (No condensation or freezing)	
Standards			UL/CSA (E216656), CE, RoHS	
Piping	Port size		Rc1/4, NPT1/4, G1/4	
	Materials of parts in contact with fluid		Sensor pressure receiving area: Silicon Piping port: C3604 (Electroless nickel plating), O-ring: HNBR	
Weight	Body	Port size Rc1/4	153 g	
		Port size NPT1/4	152 g	
		Port size G1/4	150 g	
	Lead wire with connector		139 g	
Communication (IO-Link mode)	IO-Link type		Device	
	IO-Link version		V1.1	
	Communication speed		COM2 (38.4 kbps)	
	Configuration file		IODD file*5	
	Minimum cycle time		2.3 ms	
	Process data length		Input data: 2 bytes, Output data: 0 byte	
	On request data communication		Yes	
	Data storage function		Yes	
	Event function		Yes	
Vendor ID		131 (0 x 0083)		

*1 Value without digital filter (at 0 ms)

*2 If the applied pressure fluctuates around the set value, the hysteresis must be set to a value more than the amount of fluctuation, or chattering will occur.

*3 Setting is only possible for models with the unit selection function. Only MPa or kPa is available for models without this function.

*4 The response time indicates when the set value is 90% in relation to the step input.

*5 The configuration file can be downloaded from the SMC website, <http://www.smcworld.com>

* Products with tiny scratches, marks, or display color or brightness variations which do not affect the performance of the product are verified as conforming products.

High-Precision Digital Pressure Switch: For General Fluids

ISE70G/75G/76G/77G Series

How to Order



ISE70G - 02 - L2 - M

Pressure range

Symbol	Description
ISE70G	0 to 1 MPa
ISE75G	0 to 2 MPa
ISE76G	0 to 5 MPa
ISE77G	0 to 10 MPa

Piping specification

Symbol	Description
02	Rc1/4
N02	NPT1/4
F02	G1/4*1

*1 ISO 1179-1 compliant

Orifice

Symbol	Description
Nil	None
T	Yes*1

*1 Orifice is shipped together with the product.

Output specification*1

Symbol	Description
L2	IO-Link: Switch output 1 + Switch output 2 (Switch output: NPN or PNP switching type)

*1 Refer to pages 9 and 10 for details.

Unit specification

Symbol	Description
Nil	Unit selection function*1
M	SI unit only*2

*1 Under the New Measurement Act, switches with the unit selection function are not permitted for use in Japan.

*2 Fixed unit: MPa, kPa

Option 3

Symbol	Description
Nil	Operation manual
Y	None
K	Operation manual + Calibration certificate
T	Calibration certificate

Option 2








Symbol	Description
Nil	None
A	Bracket A (Interchangeable with ISE75(H))
B	Bracket B

Option 1

Symbol	Description
Nil	None
S	Lead wire with M12 connector (Straight, 5 m)
L	Lead wire with M12 connector (Right-angled, 5 m)

Options/Part Nos.

When only optional parts are required, order with the part numbers listed below.

Description	Part no.	Note
Orifice 	ZS-48-A	 Without orifice  With orifice
Bracket A 	ZS-50-A	Interchangeable with ISE75(H) With 2 mounting screws (M4 x 6L)
Bracket B 	ZS-50-B	With 2 mounting screws (M4 x 6L)
Lead wire with M12 connector: Straight 	ZS-31-B	Lead wire length: 5 m
Lead wire with M12 connector: Right-angled 	ZS-31-C	Lead wire length: 5 m

ISE70G/75G/76G/77G Series

For pressure switch precautions and specific product precautions, refer to the "Operation Manual" on the SMC website.

Specifications

Model			ISE70G	ISE75G	ISE76G	ISE77G
Applicable fluid			Liquid or gas that will not corrode materials of parts in contact with fluid			
Pressure	Rated pressure range		0 to 1.000 MPa	0 to 2.000 MPa	0 to 5.00 MPa	0 to 10.00 MPa
	Display/Set pressure range		−0.105 to 1.050 MPa	−0.105 to 2.100 MPa	−0.25 to 5.25 MPa	−0.50 to 10.50 MPa
	Display/Smallest settable increment		0.001 MPa	0.001 MPa	0.01 MPa	0.01 MPa
	Withstand pressure		3.0 MPa	5.0 MPa	12.5 MPa	30 MPa
Power supply	Power supply voltage	When used as a switch output device	12 to 24 VDC ±10% with 10% voltage ripple or less			
		When used as an IO-Link device	18 to 30 VDC, including ripple (p-p) 10%			
	Current consumption		35 mA or less			
	Protection		Polarity protection			
Accuracy	Display accuracy		±2% F.S. ±1 digit (Ambient temperature of 25 ±3°C)			
	Repeatability		±0.5% F.S.			
	Temperature characteristics (25°C standard)		±3% F.S.	±5% F.S.		
Switch output (SIO mode)	Output type		Select from NPN or PNP open collector output.			
	Output mode		Hysteresis, Window comparator, Error output, Output OFF			
	Switch operation		Normal output, Reversed output			
	Maximum load current		80 mA			
	Maximum applied voltage		30 V (NPN output)			
	Internal voltage drop (Residual voltage)		1.5 V or less (at load current of 80 mA)			
	Delay time*1		2 ms or less, variable from 0 to 60 s/0.01 s increments			
	Hysteresis	Hysteresis mode	Variable from 0*2			
		Window comparator mode				
	Short circuit protection		Yes			
Display	Unit*3		MPa, kPa, kgf/cm², bar, psi			
	Display type		LCD			
	Number of screens		3-screen display (Main screen, Sub screen x 2)			
	Display color		Main screen: Red/Green, Sub screen: Orange			
	Number of display digits		Main screen: 4 digits (7 segments), Sub screen: 4 digits (Upper 1 digit 11 segments, 7 segments for other)			
	Indicator light		Lights up when switch output is turned ON (OUT1, OUT2: Orange)			
Digital filter*4			Variable from 0 to 30 s/0.01 s increments			
Environment	Enclosure		IP67			
	Withstand voltage		500 VAC for 1 minute between terminals and housing			
	Insulation resistance		50 MΩ or more (500 VDC measured via megohmmeter) between terminals and housing			
	Operating temperature range		Operating: −5 to 50°C, Stored: −10 to 60°C (No condensation or freezing)			
	Operating humidity range		Operating/Stored: 35 to 85% RH (No condensation)			
Standards			UL/CSA (E216656), CE, RoHS			
Piping	Port size		Rc1/4, NPT1/4, G1/4			
	Materials of parts in contact with fluid		Sensor pressure receiving area: Al2O3 (Alumina 96%), Piping port: C3604 (Electroless nickel plating), O-ring: FKM + Grease (1 MPa), Square ring: FKM (2, 5, 10 MPa)			
Weight	Body	Port size Rc1/4	184 g			
		Port size NPT1/4	183 g			
		Port size G1/4	181 g			
	Option	Lead wire with connector	139 g			
		Bracket A	17.7 g			
		Bracket B	14.2 g			
		Orifice	1.2 g			
Communication (IO-Link mode)	IO-Link type		Device			
	IO-Link version		V1.1			
	Communication speed		COM2 (38.4 kbps)			
	Configuration file		IODD file*5			
	Minimum cycle time		2.3 ms			
	Process data length		Input data: 2 bytes, Output data: 0 byte			
	On request data communication		Yes			
	Data storage function		Yes			
	Event function		Yes			
	Vendor ID		131 (0 x 0083)			

*1 Value without digital filter (at 0 ms)

*2 If the applied pressure fluctuates around the set value, the hysteresis must be set to a value more than the amount of fluctuation, or chattering will occur.

*3 Setting is only possible for models with the unit selection function. For models without this function, only MPa or kPa is available for the ISE70G/ISE75G, and only MPa is available for the ISE76G/ISE77G.

*4 The response time indicates when the set value is 90% in relation to the step input.



*5 The configuration file can be downloaded from the SMC website, <http://www.smcworld.com>

* Products with tiny scratches, marks, or display color or brightness variations which do not affect the performance of the product are verified as conforming products.

Set Pressure Range and Rated Pressure Range

Set the pressure within the rated pressure range. The set pressure range is the range of pressure within which switch output can be set. The rated pressure range is the range of pressure that satisfies the specifications (accuracy, linearity, etc.) of the product. Although it is possible to set a value outside the rated pressure range, the specifications cannot be guaranteed even if the value stays within the set pressure range.

Switch		Pressure range					
		-0.1 MPa	0	1 MPa	2 MPa	5 MPa	10 MPa
For 1 MPa (For air and general fluids)	ISE70		0	1 MPa			
	ISE70G	-0.105 MPa		1.05 MPa			
For 1.6 MPa (For air)	ISE71		0	1.6 MPa			
		-0.105 MPa		1.68 MPa			
For 2 MPa (For general fluids)	ISE75G		0	2 MPa			
		-0.105 MPa		2.1 MPa			
For 5 MPa (For general fluids)	ISE76G		0	5 MPa			
		-0.25 MPa		5.25 MPa			
For 10 MPa (For general fluids)	ISE77G		0	10 MPa			
		-0.50 MPa		10.5 MPa			


 Rated pressure range of the switch
 Set pressure range of the switch

Internal Circuits and Wiring Examples


When used as a switch output device

* The numbers in the circuit diagrams show the connector pin layout.


Setting of NPN open collector 2 outputs



Setting of PNP open collector 2 outputs




When used as an IO-Link device




ISE7□/7□G Series

Dimensions


Without bracket




Bracket A (Interchangeable with ISE70/ISE75(H)) (Part no.: ZS-50-A)




Bracket B (Part no.: ZS-50-B)



Lead wire with M12 connector (Part no.: ZS-31-B)



(Part no.: ZS-31-C)



When used as a switch output device

No.	Description	Lead wire color	Note
1	DC(+)	Brown	12 to 24 VDC
2	OUT2	White	Switch output 2
3	DC(-)	Blue	0 V
4	OUT1	Black	Switch output 1

When used as an IO-Link device



No.	Description	Lead wire color	Note
1	L+	Brown	18 to 30 VDC
2	DO	White	Switch output 2
3	L-	Blue	0 V
4	C/Q	Black	Communication data (IO-Link)/ Switch output 1 (SIO)

ISE7□/7□G Series



Function Details

Display examples of the main and sub (set value) screens of each mode.



Hysteresis mode Normal output





Hysteresis mode Reversed output



Window comparator mode Normal output



Window comparator mode Reversed output



Function Details

A Auto-preset function (F4) * When using with IO-Link, the set values cannot be changed by communication.

Auto-preset function, when selected in the initial setting, calculates and stores the set value from the measured pressure.

Using this function is possible to automatically determine the optimum set value based on the variation in measured pressure due to the repeated operation of the device.

Formula for Obtaining the Set Value


Set value (Threshold value)	Hysteresis value
$P_1(P_2) = A - (A-B)/4$	$H_1(H_2) = (A-B)/2 $
$n_1(n_2) = B + (A-B)/4$	

A: Maximum pressure value in auto preset mode

B: Minimum pressure value in auto preset mode

B Display value fine adjustment function (F6)

Fine adjustment of the indicated value of the pressure sensor can be made within the range of $\pm 5\%$ of the read value. (The scattering of the indicated value can be eliminated.)



— Indicated value at a time of shipment
 - - - Adjustable range of display value fine adjustment function

* When the display value fine adjustment function is used, the set pressure value may change ± 1 digit.

C Peak/Bottom value indication function

This function constantly detects and updates the maximum (minimum) pressure when the power is supplied, and allows to hold the maximum (minimum) pressure value.

The held value is maintained even if the power supply is cut.

When the SET and DOWN buttons are simultaneously pressed for 1 second or longer, while “holding”, the held value will be reset.

D Keylock function

Prevents operation errors such as accidentally changing setting values.

E Zero-clear function

This function clears and resets the zero value on the display of measured pressure.

The indicated value can be adjusted within $\pm 7\%$ F.S. of the pressure at a time of shipment from the factory.

F Error display function

This function is to display error location and content when a problem or error has occurred.

Error name	Display	Description	Action
Over current error	Er 1 o.c.1	The load current applied to the switch output has exceeded the maximum value.	Eliminate the cause of the over current by turning off the power supply and then turn it on again.
Residual pressure error	Er 3 Zero	During zero-clear operation, pressure over $\pm 7\%$ F.S. is present. Note that the mode is returned to measurement mode automatically 1 second later. The zero clear range varies by $\pm 1\%$ F.S. due to variation between individual products.	Perform zero-clear operation again after restoring the applied pressure to an atmospheric pressure condition.
Applied pressure error	HHH	Supply pressure exceeds the maximum set pressure.	Reset applied pressure to a level within the set pressure range.
	LLL	Supply pressure is below the minimum set pressure.	
System error	Er 0 Er 7 Er 4 Er 8 Er 6 Er 9	Internal data error	Turn the power off and then on again. If the error cannot be solved, please contact SMC for investigation.
IO-Link master version error	Er 15 P.10	IO-Link version does not match that of the master. The master uses version 1.0.	Ensure that the master IO-Link version matches the device version.

If the error cannot be solved after the instructions above are performed, or errors other than those above are displayed, please contact SMC for investigation.


Function Details

G Anti-chattering function (Simple setting mode or F1, F2)

A function to delay the switch output response time to prevent chattering or prevent the detection of temporary changes in source pressure. For example, large bore cylinders and ejectors consume a large volume of air in operation, therefore, the source pressure may decrease temporarily. The delay time can be set in the range of 0.00 to 60.00 [s] in 0.01 [s] increments.

<Principle>

This function averages pressure values measured during the response time set by the user and then compares the average pressure value with the pressure set point value to output the result on the switch.



H Unit selection function (F0)

Display units can be switched with this function.

Model	Rated pressure range	Smallest settable increment				
		MPa	kPa	kgf/cm ²	bar	psi
ISE70/70G	0 to 1 MPa	0.001	1	0.01	0.01	0.1
ISE71	0 to 1.6 MPa					0.2
ISE75G	0 to 2 MPa					
ISE76G	0 to 5 MPa	0.01		0.1	0.1	1
ISE77G	0 to 10 MPa					

I Zero cut-off setting (F14)

When the pressure display value is close to zero, this function forces the display to zero.

The range to display zero can be changed within the range of 0.0 to 10.0%.

Example: When the ISE70 (1 MPa range), zero-cut value = 1.0%, 0 is displayed in the range of -9 to 9 kPa.

J Power-saving mode (F80)

Power saving mode can be selected.

It shifts to the power-saving mode without button operation for 30 seconds.

It is set to the normal mode (Power-saving mode is OFF.) at a time of shipment from the factory.

(During power-saving mode, [ECo] will flash in the sub screen and the operation light is ON (only when the switch is ON).)


K Setting of security code (F81)


Users can select whether a security code must be entered to release key lock.


At a time of shipment from the factory, it is set such that the security code is not required.

Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “**Caution**,” “**Warning**” or “**Danger**.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)*1), and other safety regulations.

 **Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.

 **Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.

 **Danger :** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.

*1) ISO 4414: Pneumatic fluid power – General rules relating to systems.
ISO 4413: Hydraulic fluid power – General rules relating to systems.
IEC 60204-1: Safety of machinery – Electrical equipment of machines.
(Part 1: General requirements)
ISO 10218-1: Manipulating industrial robots – Safety.
etc.

Warning

1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalog information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

4. Contact SMC beforehand and take special consideration of safety measures if the product is to be used in any of the following conditions.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Installation on equipment in conjunction with atomic energy, railways, air navigation, space, shipping, vehicles, military, medical treatment, combustion and recreation, or equipment in contact with food and beverages, emergency stop circuits, clutch and brake circuits in press applications, safety equipment or other applications unsuitable for the standard specifications described in the product catalog.
3. An application which could have negative effects on people, property, or animals requiring special safety analysis.
4. Use in an interlock circuit, which requires the provision of double interlock for possible failure by using a mechanical protective function, and periodical checks to confirm proper operation.

Caution

1. The product is provided for use in manufacturing industries.

The product herein described is basically provided for peaceful use in manufacturing industries.
If considering using the product in other industries, consult SMC beforehand and exchange specifications or a contract if necessary.
If anything is unclear, contact your nearest sales branch.

Limited warranty and Disclaimer/ Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”.

Read and accept them before using the product.

Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.*2)
Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided.
This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalog for the particular products.

*2) Vacuum pads are excluded from this 1 year warranty.

A vacuum pad is a consumable part, so it is warranted for a year after it is delivered.
Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

Caution

SMC products are not intended for use as instruments for legal metrology.

Measurement instruments that SMC manufactures or sells have not been qualified by type approval tests relevant to the metrology (measurement) laws of each country. Therefore, SMC products cannot be used for business or certification ordained by the metrology (measurement) laws of each country.

Revision History

Edition B * The ISE7□G for general fluids has been added.
* Number of pages has been increased from 12 to 16.

WQ

Safety Instructions

Be sure to read the “Handling Precautions for SMC Products” (M-E03-3) and “Operation Manual” before use.