

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

Issued to: SMC CORP
4-14-1 SOTO-KANDA
CHIYODA-KU, Tokyo 101-0021
Japan

This is to certify that representative samples of NKPZ2 - Motor Controllers, Float- and Pressure-operated - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 508, 18th Ed., Issue Date: 2018-3-30, Revision Date: 2021-7-8

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
ISE10, followed by M5, M5R, 01 or N01, followed by A, B, C, D, E or F, followed by Nil, M, or P, may or may not be followed by additional suffixes.	Digital pressure switches, Class 2
ISE30, followed by -01, -T1, -N3H, -C4H, -C6H, -N7H, -N3L, -C4L, -6CL or -N7L, followed by -25, 26, 28 or 65, may or may not be followed by -M, may or may not be followed by L, may or may not be followed by A, B or D.	Digital pressure switches, Class 2
ISE30A, followed by -01, N01, C4H, C6H, N7H, C4L, C6L, OR N7L, followed by N, P, A, B, C, D, E, or F, may or not be followed by M, or P, may or not be followed by L, or G, may or not be followed by A1, A2, B, D, E, or F, may or not be followed by Y, W, K, T, or R. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 100 or -X and 500 thru 999).	Digital pressure switches, Class 2
ISE35 series , ISE35, followed by -N, or -R, followed by -25, -65, -26 or -28, may or may not be followed by -M, or -P, may or may not be followed by L, may or may not be followed by A or B, may or may not be followed by -S.	Digital pressure switches
ISE40A, followed by 01, N01, W1, WF1, C4, C6 or M5, followed by R, T, S, V, X or Y, followed by Nil, M, or P, may or may not be followed by additional suffixes. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches Class 2
ISE40A, followed by -01 or -N01, followed by -N or -P, followed by -Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
ISE7, followed by 0, 5 or 5H, followed by -02, -F02 or -N02, followed by -43, -27, -67, -20, -29, -60, -69, -44, -45, -46, -47, -48, -25, -26, -28 or 65, may or may not be followed by hyphen and may or may not be followed by M or P, may or may not be followed by S or L, may or may not be followed by A.	Digital pressure switches
ISE70, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -F02 or -N02, followed by AB, L2, S1 or SV, may be followed by M, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.	Digital pressure switches, Class 2


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

<p>ISE70G, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -02T, -F02, -F02T, -N02 or -N02T, followed by AB, L2, SI or SV, may be followed by M or P, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE71, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -F02 or -N02, followed by AB, L2, SI or SV, may be followed by M, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE75G, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -02T, -F02, -F02T, -N02 or -N02T, followed by AB, L2, SI or SV, may be followed by M or P, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE76G, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -02T, -F02, -F02T, -N02 or -N02T, followed by AB, L2, SI or SV, may be followed by M or P, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE77G, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -02T, -F02, -F02T, -N02 or -N02T, followed by AB, L2, SI or SV, may be followed by M or P, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE78G, with or without prefix one or two digit(s) number with or without A and followed by "-", followed by -02, -02T, -F02, -F02T, -N02 or -N02T, followed by AB, L2, SI or SV, may be followed by M or P, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by "-X", may be followed by one digit number or 3 digits number over 500.</p>	<p>Digital pressure switches, Class 2</p>
<p>ISE79S, followed by -02, -F02, -F02T, -N02 or -N02T, followed by -L2, -SI or -SV, may be followed by M, may be followed by L or S, may be followed by A or B, may be followed by K, T or Y, may be followed by -X1 through -X9 or -X500 through -X999.</p>	<p>Digital pressure switches, Class 2</p>

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services




UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

ISE8, followed by 0 or 5, may or not be followed by F, H, M, or G, followed by -02, -N02, -F02, -C01, -A2, or -B2, may or not be followed by L, followed by -N, -P, -K, W, -A, -B, -C, -D, -E, -F, -R, -T, -S, -V, may or not be followed -M or P, may or not be followed A, B, C, or D, may or not be followed by Y, W, K, T, or R.	Digital pressure switches
ISE80, followed by -02, -N02, -F02, -C01, -A2, or -B2, followed by -A or -B, followed A, B, C, or D, followed by -Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
ISE80H, followed by -02, -N02, -F02, -C01, -A2, or -B2, followed by -A or -B, followed A, B, C, or D, followed by -Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
PSE3, followed by 0 or 1, followed by 0, 1, 2, 3, 4, or 5, may or may not be followed by T, may or may not be followed by -M, may or may not be followed by E or L, may or may not be followed by A, B, or D, may or may not be followed by C.	Pressure sensor controller
PSE300A series , PSE3, with or without prefix one or two digit(s) number with or without A, and followed by 0 or 1, followed by 0, 1, 3, 4 or 6, followed by A, followed by "-", may be followed by M, may be followed by L, may be followed by A, B or D, may be followed by C, may be followed by "-X", may be followed by one or two digit number or 3 digits number over 500.	Pressure sensor controller
PSE30, followed by 0, 1, 2, 3, 4, or 5, may or may not be followed by M, may or may not be followed by L, may or may not be followed by A, B, or D, may or may not be followed by C.	Pressure sensor controller
PSE54, , with or without prefix one or two digit(s) number with or without A, and followed by 0, 1 or 3, may or may not be followed by A, followed by -01, -IM5, -IM5H, -M3, -M5, -N01, -R04 or -R06, may be followed by L, N, P, may be followed by -C2 or -S, may be followed by X, may be followed by 1 to 9 or 500 to 999.	Pressure sensor
PSE55, followed by 0, 1, 2, 3, or 4, may or may not be followed by F, may or may not be followed by -28, may or may not be followed by -A, may or may not be followed by C2.	Low Differential Pressure Sensor
PSE56, followed by 0, 1, 3, or 4, followed by -01, -02, -NO1, -NO2, -C01, -F02, -A2 or B2, may or may not be followed by -28, may or may not be followed by -C1 or -C2.	Pressure sensor


 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

ZSE10, followed by M5, M5R, 01 or N01, followed by A, B, C, D, E or F, followed by Nil, M, or P, may or may not be followed by additional suffixes.	Digital pressure switches, Class 2
ZSE10F, followed by M5, M5R, 01 or N01, followed by A, B, C, D, E or F, followed by Nil, M, or P, may or may not be followed by additional suffixes.	Digital pressure switches, Class 2
ZSE30, followed by -01, -T1, -N3H, -C4H, -C6H, -N7H, -N3L, -C4L, -6CL or -N7L, followed by -25, 26, 28 or 65, may or may not be followed by -M, may or may not be followed by L, may or may not be followed by A, B or D.	Digital pressure switches, Class 2
ZSE30A, followed by -01, N01, C4H, C6H, N7H, C4L, C6L, OR N7L, followed by N, P, A, B, C, D, E, or F, may or not be followed by M, or P, may or not be followed by L, or G, may or not be followed by A1, A2, B, D, E, or F, may or not be followed by Y, W, K, T, or R. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 100 or -X and 500 thru 999).	Digital pressure switches, Class 2
ZSE30AF, followed by -01, N01, C4H, C6H, N7H, C4L, C6L, OR N7L, followed by N, P, A, B, C, D, E, or F, may or not be followed by M, or P, may or not be followed by L, or G, may or not be followed by A1, A2, B, D, E, or F, may or not be followed by Y, W, K, T, or R. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 100 or -X and 500 thru 999).	Digital pressure switches, Class 2
ZSE40A, followed by 01, N01, W1, WF1, C4, C6 or M5, followed by R, T, S, V, X or Y, followed by Nil, M, or P, may or may not be followed by additional suffixes. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches Class 2
ZSE40A followed	Digital pressure switches, Class 2
ZSE40A, followed by -01 or -N01, followed by -N or -P, followed by -Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
ZSE40AF, followed by 01, N01, W1, WF1, C4, C6 or M5, followed by R, T, S, V, X or Y, followed by Nil, M, or P, may or may not be followed by additional suffixes. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches Class 2
ZSE40AF, followed by -01 or -N01, followed by -N or -P, followed by -Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
ZSE8, followed by 0 or 5, may or not be followed by F, H, M, or G, followed by -02, -N02, -F02, -C01, -A2, or -B2, may or not be followed by L, followed by -N, -P, -K, W, -A, -B, -C, -D, -E, -F, -R, -T, -S, -V, may or not be	Digital pressure switches

Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L216656-21-51501002-6
Report Reference E216656-20010515
Date 8-Dec-2023

followed -M or P, may or not be followed A, B, C, or D, may or not be followed by Y, W, K, T, or R.	
ZSE80, followed by -02, -N02, -F02, -C01, -A2, or -B2, followed by -A or -B, followed A, B, C, or D, followed by - Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2
ZSE80F, followed by -02, -N02, -F02, -C01, -A2, or -B2, followed by -A or -B, followed A, B, C, or D, followed by - Nil, -M, or -P, followed by L. With or without Prefix (1 through 99 and hyphen) or suffix (-X and 1 thru 9 or -X and 500 thru 999).	Digital pressure switches, Class 2

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

